


HYDRAULIC HAMMERS / HYDRAULIKHÄMMER

FX SERIES PRO



			FX-6 PRO	FX-25 PRO	FX-35 PRO	FX-45 PRO	FX-55 PRO	FX-65 PRO	FX-75 PRO	FX-95 PRO	FX-110 PRO	FX-130 PRO	FX-170 PRO
(1)	Baggerklasse/Excavatorclass	T.	0,5-1,2	1,0 - 2,4	2,0 - 3,8	2,6 - 4,5	3,6 - 6,5	5 - 8,5	6,5-10	9-15	12-18	14-21	16-24
	Gewicht / Weight	Kg.	60	122	195	260	345	470	570	840	930	1190	1420
	Langer Schlag / long stroke	S/Min.	800-1200	550-1000	600-1500	550-1300	380-1100	400-800	350-700	350-600	350-550	350-550	320-500
	Kurzer Schlag / short stroke	S/Min.	-	-	-	-	-	600-1100	490-1000	600-900	600-900	400-700	400-650
	Arbeitsdruck / Workingpressure	Bar	60-130	90-120	90-120	110 - 165	120-165	140-170	140-170	140-180	140-180	160-190	160-190
	Einstelldruck Bagger / Excavator pressure	Bar	100-170	130-160	130-160	150 - 205	160-205	190-210	190-210	190-220	190-220	200-230	200-230
	Ölvolumenstrom / Oilflow	L/min.	18-25	15-35	23 - 70	35 - 70	40 - 110	45-100	50-110	75-120	80-140	100-150	100-155
	Meißel Diameter/Chisel diameter	mm.	40	45	57	70	75	80	90	95	105	115	125

			FX-190 PRO	FX-210 PRO	FX-260 PRO	FX-320 PRO	FX-380 PRO	FX-460 PRO	FX-520 PRO	FX-680 PRO	FX-740 PRO	FX-820 PRO	FX-1200 PRO
(1)	Baggerklasse/Excavatorclass	T.	18-26	20-28	24-32	25-36	30-42	34-50	42-60	47-78	60-90	65-100	88-150
	Gewicht / Weight	Kg.	1560	1820	2050	2380	2800	3200	3800	4600	5800	7100	10400
	Langer Schlag / long stroke	S/Min.	320-480	340-450	270-400	250-380	230-400	230-345	230-330	270-380	280-355	280-350	250-320
	Kurzer Schlag / short stroke	S/Min.	400-600	420-550	330-500	300-450	270-470	270-410	270-550	380-530	380-485	320-520	290-380
	Arbeitsdruck / Workingpressure	Bar	160-190	160-190	160-190	160-190	160-190	160-190	160-190	160-190	160-190	160-190	160-190
	Einstelldruck Bagger / Excavator pressure	Bar	200-230	200-230	200-230	200-230	200-230	200-230	200-230	200-230	200-230	200-230	200-230
	Ölvolumenstrom / Oilflow	L/min.	120-170	120-190	150-210	180-240	200-260	220-280	240-320	260-360	310-390	360-450	450-530
	Meißel Diameter/Chisel diameter	mm.	135	135	145	150	155	165	175	180	200	205	240

(1) Recommended excavator / attachment combination

(1) Empfohlene Bagger/Anbauteil Kombination



Soundproofed Schallschutz

Vibration Damper Vibrations Dämpfer

Bigger Nitrogen chamber Größeres Gas Raum

Frequency valve Frequenz Ventil

Bigger control valve Größeres Ventil

Auto Lube Auto-Lube Schmiersystem

Accumulator Akkumulator

Heavy Duty Housing Heavy Duty Gehäuse

Retainer pin Sperrachse

Piston Schlagkolben

Chisel Meißel



Hydraram FX-Series Pro

- AutoLubrication
- AutoStop
- DustControl
- PowerSelect
- VibrosilencedPro
- EnergieRecovery



Hydraram FX-Series Pro

- AutoSchmierung
- AutoStop
- StaubStop
- PowerSelect
- VibrosilencedPro
- EnergieRückgewinnung