



CORPORATE BROCHURE



COMBI CUTTERS / KOMBISCHEREN








HCS SERIES



 7 MODELS COMBI CUTTERS FROM 980 UP TO 11.200 KGS FOR EXCAVATORS FROM 10 ~ 150 TONS

 7 MODELLE KOMBISCHEREN VON 980 BIS ZU 11.200 KG FÜR BAGGER VON 10 BIS ZU 150 TONNEN



		HCS-12U	HCS-19U	HCS-28U	HCS-38U	HCS-48U	HCS-72U	HCS-110U	
 (1)	Baggerklasse/Excavatorclass	T.	10-16	17-25	24-37	32-50	42-62	52-86	86-150
	Gewicht / Weight	Kg.	980	1980	2960	3820	4820	7180	11200
-	Maulweite / Jaw opening	mm.	670	760	890	1050	1360	1430	1950
-	Maultiefe / Jaw depth	mm.	340	625	745	785	1100	1170	1320
-	Blade length / Messerlänge	mm.	140	350	350	525	525	525	720
-	Schneidkraft / Cutting force	T.	208	240	385	530	640	1025	1390
-	Brechkraft / Crushing force	T.	58	62	98	116	162	186	240
	Arbeitsdruck Bagger / Workingpressure excavator	Bar	380	380	380	380	380	380	380
	Ölvolumenstrom / Oilflow	L/min.	90-180	150-250	150-250	230-360	350-450	450-550	500-800
	Öffnen/Schließen (sek.) / Open/close (sec.)	Sec.	2.0/2.2	1.5/1.6	2.7/3.0	2.8/3.0	3.1/3.5	3.7/3.7	3.8/3.9
	Arbeitsdruck beim rotieren / Workingpressure rotation	Bar	180	180	180	180	180	180	180
	Ölvolumenstrom beim rotieren / Oilflow rotation	L/min.	25	30	30	50	50	50	50

